

Self Drillers

Self Drilling Screws manufactured with a 6-Lobe Pin drive.



Drilling tips provide fast and easy application eliminating the need to pre-drill. Installed and removed using 6-Lobe Pin tooling.

- Stocked in Delta Protekt® Coated Steel



6-Lobe Pin Tooling



Countersunk Head



Pan Head

Stock Range:

Countersunk Head

Box Qty 100

Length Gauge		1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	■	■	■	■		T20
10	4.8mm		■	■	■	■	T25
12	5.5mm			■	■	■	T27

Pan Head

Box Qty 100

Length Gauge		1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	■	■	■	■		T20
10	4.8mm		■	■	■	■	T25
12	5.5mm			■	■	■	T27

Drill Point Information:

Gauge (Point size)	8 (2)	10 (3)	12 (3)
Material thickness Mild steel up to (mm)	1 + 2	2 + 2	2 + 3

All sizes shown are without min and max tolerances and are guide sizes.