

Hexagon socket screws manufactured with an internal pin.

This drive prevents removal with standard hexagon tools. Suitable for medium torque applications and is one of the most difficult to remove without the matching driver.

- Full range of AB Self Tapping and Metric Machine Screws stocked in A2 Stainless Steel
- Other styles of fasteners in the Pin Hex drive system: Socket Cap Screws, Grub Screws and Barrel Nuts

Countersunk  
A2 Self  
Tapper



Button Head  
A2 Self Tapper

Countersunk A2  
Machine  
Screw



Button Head  
A2 Machine Screw



Pin Hex Tooling



Raised  
Countersunk  
A2 Machine Screw

## Stock Range:

Countersunk / Button Head | AB Type Self Tapping Screws Box Qty 100

| Length<br>Gauge | 3/8"  | 1/2" | 5/8" | 3/4" | 1"   | 1 1/4" | 1 1/2" | 2"   | 2 1/2" | 3"   | DRIVER<br>SIZE |
|-----------------|-------|------|------|------|------|--------|--------|------|--------|------|----------------|
|                 | 9.5mm | 13mm | 16mm | 19mm | 25mm | 32mm   | 38mm   | 50mm | 63mm   | 75mm |                |
| 6               | 3.5mm | ■    | ■    | ■    | ■    |        | ■      |      |        |      | 2mm            |
| 8               | 4.2mm | ▲    | ■    | ■    | ■    | ■      | ■      | ■    |        |      | 2.5mm          |
| 10              | 4.8mm |      | ■    | ■    | ■    | ■      | ■      | ■    | ■      |      | 3mm            |
| 12              | 5.5mm |      |      |      | ■    | ■      | ■      | ■    |        |      | 4mm            |
| 14              | 6.3mm |      |      |      | ■    | ■      | ■      | ■    |        |      | 4mm            |

Countersunk / Raised Countersunk / Button Head |  
Metric Machine Screws

Box Qty 100

| Length<br>Gauge | 6 mm | 8 mm | 10 mm | 12 mm | 16 mm | 20 mm | 25 mm | 30 mm | 35 mm | 40 mm | 45 mm | 50 mm | 60 mm | 80 mm | 100 mm | 120 mm | DRIVER<br>SIZE |
|-----------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|--------|----------------|
|                 |      |      |       |       |       |       |       |       |       |       |       |       |       |       |        |        |                |
| M3              | ■    |      | ■     | ■     | ■     | ■     |       |       |       |       |       |       |       |       |        |        | 2mm            |
| M3.5            |      |      |       | ★     |       | ★     | ★     | ★     |       | ★     |       | ★     | ★     |       |        |        | H30            |
| M4              | ▲    | ■    | ■     | ■     | ■     | ■     | ■     | ■     |       | ■     |       |       |       |       |        |        | 2.5mm          |
| M5              |      | ▼    | ■     | ■     | ■     | ■     | ■     | ■     |       | ■     |       | ■     | ■     |       |        |        | 3mm            |
| M6              |      | ▼    | ■     | ■     | ■     | ■     | ■     | ■     |       | ■     |       | ■     | ■     |       |        |        | 4mm            |
| M8              |      |      |       | ■     | ■     | ■     | ■     | ■     | ■     | ■     | ▼     | ■     | ■     |       |        |        | 5mm            |
| M10             |      |      |       |       | ▲     | ■     | ■     | ■     |       | ■     |       | ■     | ■     |       | ▲      |        | 6mm            |
| M12             |      |      |       |       |       | ■     | ■     | ■     | ▲     | ■     |       | ■     | ■     | ▲     | ▲      | ▲      | 8mm            |

### Head Styles

- ▼ Countersunk only
- ★ Raised Countersunk only
- ▲ Button Head only
- Countersunk & Button Head