



Lightweight Metric Keenserts

Lightweight Metric Inserts - Non-Locking													
PART NO.	DIMENSIONS					INSTALLATION						REMOVAL	
NON-LOCKING	INTERNAL THREAD CLASS 5H	EXTERNAL THREAD		L ⌀ 0.3	A	TAP DRILL DIAMETER	C'SINK DIAMETER +.25/-00	THREAD TAP		INSTALLATION TOOL PART NO.	ALTERNATE INSTALLATION TOOL	DRILL	
		SIZE CLASS 4H	SHEAR ENGAG.					SIZE CLASS 6H	MIN. DEPTH			SIZE	DEPTH
KNM 5x0.8	M 5x0.8	M 8x1.25	104.9	8.0	-	6.9	8.25	M 8x1.25	9.5	LDSM5	TM-5*	5.50	4.00
KNM 6x1.0	M 6x1.0	M 10x1.25	177.7	10.0	-	8.8	10.25	M 10x1.25	11.5	LDSM6	TM-6*	7.50	4.75
KNM 8x1.25	M 8x1.25	M 12x1.25	266.7	12.0	-	10.8	12.25	M 12x1.25	13.5	LDSM8	TM-8*	9.50	
KNM 8x1.0	M 8x1.0	M 12x1.25	266.7	12.0	-	10.8	12.25	M 12x1.25	13.5	LDSM8	TM-8*	9.50	
KNM 10x1.5	M 10x1.5	M 14X1.5	341.6	14.0	-	12.8	14.25	M 14X1.5	15.5	LDSM10	TM-10*	11.50	
KNM 10x1.25*	M 10x1.25	M 14X1.5	341.6	14.0	-	12.8	14.25	M 14X1.5	15.5	LDSM10	TM-10*	11.50	
KNM 12x1.75*	M 12x1.75	M 16X1.5	470.2	16.0	-	14.75	16.25	M 16X1.5	17.5	LDSM12	TM-12*	13.50	
KNM 12x1.25*	M 12x1.25	M 16X1.5	470.2	16.0	-	14.75	16.25	M 16X1.5	17.5	LDSM12	TM-12*	13.50	
Lightweight Metric Inserts - Locking													
KNML 5x0.8	M 5x0.8	M 8x1.25	83.1	8.0	7.6	6.9	8.25	M 8x1.25	9.5	LDSM5	TM-5*	5.50	4.00
KNML 6x1.0	M 6x1.0	M 10x1.25	152.7	10.0	8.2	8.8	10.25	M 10x1.25	11.5	LDSM6	TM-6*	7.50	4.75
KNML 8x1.25	M 8x1.25	M 12x1.25	242.5	12.0	9.5	10.8	12.25	M 12x1.25	13.5	LDSM8	TM-8*	9.50	
KNML 8x1.0	M 8x1.0	M 12x1.25	242.5	12.0	9.0	10.8	12.25	M 12x1.25	13.5	LDSM8	TM-8*	9.50	
KNML 10x1.5	M 10x1.5	M 14X1.5	316.4	14.0	10.0	12.8	14.25	M 14X1.5	15.5	LDSM10	TM-10*	11.50	
KNML 10x1.25*	M 10x1.25	M 14X1.5	316.4	14.0	9.5	12.8	14.25	M 14X1.5	15.5	LDSM10	TM-10*	11.50	
KNML 12x1.75	M 12x1.75	M 16X1.5	441.4	16.0	11.20	14.75	16.25	M 16X1.5	17.5	LDSM12	TM-12*	13.50	
KNML 12x1.25*	M 12x1.25	M 16X1.5	441.4	16.0	10.20	14.75	16.25	M 16X1.5	17.5	LDSM12	TM-12*	13.50	

* Indicates minimum activity-limited availability. Minimums may apply.