

Application:

on metal sheets.

Mounting:

capacitor discharge or voltaic arc welding.





code	lengh† L +0,6	available			
		М3	M4	M5	M6
DF06	6	А			
DF07	7	0			
DF08	8	0	0		
DF10	10	0	0	0	0
DF12	12	0	0	0	0
DF15	15	0	0	0	0
DF16	16	А	Α	А	А
DF20	20	0	0	0	А
DF25	25	0	0	0	
DF30	30	А	А	0	

code	metric thread d1	external diameter d2±0,1	head diameter d3±0,2	*thread lenght l1 <u>+</u> 0,5
_5X_M3	M 3	5,0	6,5	5,0
_6X_M4	M 4	6,0	7,5	6,0
7.1XM5	M 5	7,1	9,0	7,5
8XM6	M 6	8,0	9,0	7,5

\* l1 quote of sald standoff with L dimension up to 8 mm is = 4 mm.

available steel and stainless steel

available only in steel

available only in stainless steel

In order to have an appropriate assembly it is reccomended to do some preliminary assembling tests.

Non binding dimensions, expressed in mm.

Standard

On demand

-- Not manufactured

Material: steel, stainless steel

Finishing: weld standoff in steel: copper plated

weld standoff in stainless steel: natural

Thread d1: metric ISO 6 H

weld standoff in copper plated steel, Example:


M5 thread, 25 mm lenght:

DFA 7.1X25M5

weld standoff in stainless steel,

M5 thread, 25 mm lenght: DFX 7.1X25M5







Headquarter and Export department: Strada della Pronda 66/6 - 10142 - Torino - IT - Tel. +39.011.700301 - Fax +39.011.702947 Milan branch: Via E. Cialdini 37 - 20126 - Milano - IT - Tel. +39.02.646.8476 - Fax +39.02.662.00275

Production and purchase departments:

Via E. Pavanello 1 - 30030 - Maerne di Martellago (Venezia) - IT - Tel. +39.041.503.0100 Fax +39.041.503.0110

SPECIALINSERT, COMMITS ITSELF TO CONTINUOUSLY IMPROVE ITS +
PRODUCTS IT RESERVES THE RIGHT TO CHANGE THER TECHNICAL
AND STRUCTURAL CHARACTERISTICS WITHOUT PRIOR NOTICE.
ALL RIGHTS ARE RESERVED AND THE DUPLICATE, EVEN PARTIAL,
OF THESE DOCUMENTS AS WELL AS ITS DISTRIBUTION TO THIRD PARTIES.
ARE FORBIDDEN, UNLESS OTHERWISE AND EXPRESSLY AUTHORIZED BY SPECIALINSERT.

www.specialinsert.it - export@specialinsert.it